

## AS Series Comparison Chart



Model	Machine Dimensions Length x Width x Height	Carton Range*** Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.****	Shipping Weight (lbs.)
AS12-2 <b>2" Tape Head</b>	(70.2") x (26.5") x (68.0")*	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	500
AS12-2H** <b>2" Tape Head</b>	(70.2") x (26.5") x (68.0")*	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 57	500
AS12-3 <b>3" Tape Head</b>	(70.2") x (26.5") x (68.0")*	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	500
AS12-3H** <b>3" Tape Head</b>	(70.2") x (26.5") x (68.0")*	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 57	500
AS22-2 <b>2" Tape Head</b>	(77.7") x (33.8") x (69.0")*	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	585
AS22-2H** <b>2" Tape Head</b>	(77.7") x (33.8") x (69.0")*	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 57	585
AS22-3 <b>3" Tape Head</b>	(77.7") x (33.8") x (69.0")*	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	585
AS22-3H** <b>3" Tape Head</b>	(77.7") x (33.8") x (69.0")*	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 57	585

Information subject to change without notice.

\* Safety Gates are an additional 20" Long  
 \*\* High Speed  
 \*\*\* Outside Dimensions Only  
 \*\*\*\* Based on a 12" long carton