



#### ■ Re-feed Function

The "re-feed function" resets and recycles the machine if a strap feed failure occurs.

#### ■ Easy Maintenance

JK-5 steps through the strapping cycle one operation at a time. By observing the operation of the JK-5 in this mode, it is easy to identify problems and make adjustments.

#### ■ Seal Joint Alignment

A new strap alignment device in the right bandway assures perfect strap alignment, even with 1/4" or 5mm strap.

#### ■ Compact !

Space-efficient design with internal coil dispenser.

#### ■ Newly designed Coil Brake

This innovative, elegant design provides a soft start and stop of the strap coil. The JK-5 is the most reliable machine in its class.

#### ■ Easy Strap Width Conversion

The JK-5 can be set to run 5mm to 1/2" polypropylene strap. No conversion parts are required.

### SPECIFICATIONS

Width	915mm	36"
Height	1339mm	52 3/4"
Depth	600mm	23 5/8"
Machine Weight	approx 108kg	238lbs
Table height	830mm	32 1/2"
Arch Size	W650 x H400mm	W26" x H16"
Strap Width	5, 6, 9, 12mm	5mm, 1/4", 3/8", 1/2"

Package (Max)	W620 x H380mm	W24 3/8" x 15"H
Size (Min)	W60 x H30mm	W2 3/8" x 1 1/4"H
Max Strap tension	392N(40kgf) (88 lbs.)	
Speed	up to 27straps/min	
Power	100, 110, 120, 200, 220, 230, 240v	
Supply	Single Phase 50/60Hz 0.56kw	