

## RS Series Comparison Chart



Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
RS22-2 <b>2" Tape Head</b>	(42.9") x (34.8") x (71.8")	(6.0" - U) x (4.25" - 20.0") x (4.0" - 21.0")	(20.5" - 30.0")	Up to 15	410
RS22-3 <b>3" Tape Head</b>	(42.9") x (34.8") x (71.8")	(6.0" - U) x (5.25" - 21.0") x (4.0" - 21.0")	(20.5" - 30.0")	Up to 15	410
RS23-2 <b>2" Tape Head</b>	(42.9") x (34.8") x (76.0")	(6.0" - U) x (4.5" - 20.0") x (4.0" - 30.0")	(20.5" - 30.0")	Up to 12	440
RS23-3 <b>3" Tape Head</b>	(42.9") x (34.8") x (76.0")	(6.0" - U) x (5.5" - 21.0") x (4.0" - 30.0")	(20.5" - 30.0")	Up to 12	440
RS32-2 <b>2" Tape Head</b>	(42.9") x (44.2") x (71.8")	(6.0" - U) x (4.5" - 30.0") x (4.0" - 20.5")	(20.5" - 30.0")	Up to 12	462
RS32-3 <b>3" Tape Head</b>	(42.9") x (44.2") x (71.8")	(6.0" - U) x (5.5" - 30.0") x (4.0" - 20.5")	(20.5" - 30.0")	Up to 12	462
RS33-3 <b>3" Tape Head</b>	(42.9") x (44.2") x (76.0")	(6.0" - U) x (5.5" - 30.0") x (4.0" - 30.0")	(20.5" - 30.0")	Up to 12	600

Information subject to change without notice.

U - Unlimited  
All Models available in High Speed & Stainless Steel  
\*Outside Dimensions Only