

## ELVS

### Automatic L-Type Suction Cup Case Erector

The BestPack™ Model ELVS is an innovative, high-performance carton erector/sealer. This erector is built for heavy usage with quick and simple carton size changeover. There are no tools required for carton size changeover. The ELVS handles a wide range of carton sizes.

Our ELVS erector line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



## Key Points of the Carton Sealer



**No Operator  
Required**



**Uniform Cartons**



**Bottom Seal**

## Features

- Heavy Duty 3mm Welded Frame
- Quick and Easy Changeover
- Size Adjustment Screw Drive Counter for the Hopper Height Position and Carton Width.
- Size Adjustment Screw Drive Counter for the Carton Length
- Power Feed Hopper
- Hopper Length of 40" for Carton Capacity
- Side Belt Drive with High Speed Motors
- Capable of Interchanging 2" or 3" BestPack Pop-out High Speed Tape Head
- Low Tape/No Tape on Carton/No Cut Sensors with Malfunction Alarm with Three-colored Light

- Manual Jog Button for Step-by-step Activation of All Movements
- SMC Maintenance Free, Oil-less Air Cylinders with Air Cushion
- Vacuum Pump Suction Cup System
- Omron PLC Logic
- Carton on Demand Logic
- Heavy-duty Peg Legs

## Options

- Spare Parts Kit
- Allen Bradley PLC with Ethernet Capability
- Exit Conveyor
- Food Grade 304 Stainless Steel

# Extra Accessories to Improve Efficiency



\*Spare Parts Kit May Vary\*

Spare Parts Kit



Carton Sealing Tape



Spare Tape Head



Long Exit Conveyor

- Food Grade 304 Stainless Steel

## Machine & Carton Specifications

**110 Volts 60 Hz**  
**20 AMP**  
Power Requirements

**Up to 10-15 Cartons/min.**  
Speed

**80 psi, 10 SCFM**  
Air Requirements


**1,800 lbs**  
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
ELVSL22-2H <b>2" Tape Head</b>	(100.8") x (83.0") x (64.3")	(7.5" - 25.0") x (5.0" - 20.5") x (3.0" - 21.5")	(25.5" - 31.5")	Up to 10-15	1,800
ELVSR22-2H <b>2" Tape Head</b>	(100.8") x (83.0") x (64.3")	(7.5" - 25.0") x (5.0" - 20.5") x (3.0" - 21.5")	(25.5" - 31.5")	Up to 10-15	1,800
ELVSL22-3H <b>3" Tape Head</b>	(100.8") x (83.0") x (64.3")	(7.5" - 25.0") x (5.0" - 20.5") x (3.0" - 21.5")	(25.5" - 31.5")	Up to 10-15	1,800
ELVSR22-3H <b>3" Tape Head</b>	(100.8") x (83.0") x (64.3")	(7.5" - 25.0") x (5.0" - 20.5") x (3.0" - 21.5")	(25.5" - 31.5")	Up to 10-15	1,800

Information subject to change without notice.

All Models available in Food Grade 304 Stainless Steel

ELVSL22



ELVSR22

