

Technical Specifications

NON-CONVEYORIZED TURNTABLE MODELS

CONVEYORIZED TURNTABLE MODELS

	SMLPA-200	SMHPA-300	WCA-150	WCA-200
PRODUCTION RATE*	• Up to 50 loads per hour	• Up to 55 loads per hour	• Up to 50 loads per hour	• Up to 60 loads per hour
LOAD SIZE	• Min.: 36"W x 36"L x 10"H • Max.: 50"W x 50"L x 80"H	• Min.: 36"W x 36"L x 10"H • Max.: 51"W x 51"L x 80"H	• Min.: 36"W x 36"L x 10"H • Max.: 48"W x 48"L x 76"H	• Min.: 36"W x 36"L x 10"H • Max.: 48"W x 48"L x 80"H
LOAD WEIGHT	• 5,000 lbs.	• 8,000 lbs.	• 4,000 lbs. (conveyor dependant)	• 4,000 lbs. (conveyor dependant)
MACHINE DIMENSIONS**	• 66"W x 128"L x 86 3/4"H	• 51"W x 120"L x 96"H	• 199"W x 135"L x 96"H	• 200"W x 135"L x 102 1/2"H
APPROXIMATE SHIPPING WEIGHT	• 2,800 lbs.	• 2,900 lbs.	• 4,750 lbs.	• 4,750 lbs.
ELECTRICAL REQUIREMENTS ***	• 120V/1/60 15A	• 120V/1/60 15A	• 230V/3/60 20A	• 230V/3/60 20A
PNEUMATIC REQUIREMENTS	• No external air source required; air compressor included	• 3 CFM @ 80 PSI comes with FR (Filter, Regulator)	• 3 CFM @ 80 PSI	• 3 CFM @ 80 PSI comes with FR (Filter, Regulator)
CONTROLS	• Top cover pause switch • Remote Start/Stop pull cord • Separate top and bottom wrap selection (0-9) • Separate up and down carriage speeds • Refer to Control Panel Sheet for more info	• Top cover pause switch • Remote Start/Stop pull cord • Separate top and bottom wrap selection (0-9) • Separate up and down carriage speeds • Refer to Control Panel Sheet for more info	• Intuitive alarm diagnostics • On-screen wrapping performance analysis • On-screen maintenance program and instructions • Separate top and bottom wrap selection (0-9)	• Intuitive alarm diagnostics • On-screen wrapping performance analysis • On-screen maintenance program and instructions • Separate top and bottom wrap selection (0-9)
FILM DELIVERY SYSTEM	• 20" NO-THREAD® powered pre-stretch carriage • 1/2 HP AC motor with variable frequency drive	• 20" NO-THREAD® powered pre-stretch carriage • 1/2 HP AC motor with variable frequency drive	• 20" Econo NO-THREAD® powered pre-stretch carriage • 1/2 HP AC motor with variable frequency drive	• 20" NO-THREAD® powered pre-stretch carriage • 1/2 HP AC motor with variable frequency drive
FILM TAIL TREATMENT	• Pulsed-controlled cutter • Film alignment arm and brush on film treatment & clamping • Air compressor included	• Automatic film clamping • Pulsed-controlled cutter • Film alignment arm and brush on film treatment	• Automatic film clamping • Pulsed-controlled cutter • Film alignment arm and brush on film treatment	• Automatic film clamping • Pulsed-controlled cutter • Film alignment arm and brush on film treatment
TURNTABLE DRIVE	• 12 RPM variable speed • 3/4 HP AC motor with variable frequency drive • #50 ANSI heavy-duty chain drive	• Up to 15 RPM variable speed • 1 1/2 HP AC motor with variable frequency drive • Heavy-duty ring gear bearing drive	• 12 RPM variable speed • 1 HP AC motor with variable frequency drive • Heavy-duty ring gear bearing drive	• 15 RPM variable speed • 1 1/2 HP AC motor with variable frequency drive • Heavy-duty ring gear bearing drive
STRUCTURE	• Forklift portable base design (from both ends) • Heavy-duty structural steel construction	• Forklift portable base design (from both ends) • Heavy-duty structural steel construction	• Forklift portable base design (from both ends) • Heavy-duty structural steel construction	• Forklift portable base design (from both ends) • Heavy-duty structural steel construction
WARRANTY	• 4-year unlimited cycle warranty**** • 10-year warranty on steel structure • Lifetime warranty on pre-stretch rollers' blue compound	• 4-year unlimited cycle warranty • 10-year warranty on steel structure • 10-year warranty on 25" ring gear bearings • Lifetime warranty on pre-stretch rollers' blue compound	• 3-year unlimited cycle warranty • 10-year warranty on steel structure • 10-year warranty on 25" ring gear bearings	• 3-year unlimited cycle warranty • 10-year warranty on steel structure • 10-year warranty on 25" ring gear bearings • Lifetime warranty on pre-stretch rollers' blue compound

All machine specifications are subject to change without prior notice. Nominal dimensions shown.

- * Production rate based on load size and configuration.
- ** Machine height can exceed by up to 8" when carriage is in upmost position.
- *** Other voltage available upon request.
- **** Air compressor has 1 year warranty.

Wulftec International Inc.
209 Wulftec, Ayer's Cliff, Quebec, Canada J0B 1C0
Tel: 819 838-4232
Toll Free: 1 877 WULFTEC (985-3832)
Fax: 819 838-5539
E-mail: wulftec@wulftec.com



www.wulftec.com

THE TURNTABLE SERIES

Whatever the need for a stretch wrapping system, Wulftec has an economy, heavy duty, or custom built solution to meet your specific requirements. Choose the options you want; get the rugged efficiency you need.

- NON-CONVEYORIZED
SMLPA-200
SMHPA-300
- CONVEYORIZED
WCA-150
WCA-200

Why Go Automatic?

Automatic stretch wrappers are designed to maximize throughput and efficiency. They take care of everything; all you need to do is change the roll of film. An automatic stretch wrapper will save you significant time and money.

BENEFITS OF A TURNTABLE

Turntable stretch wrappers are ideal for wrapping stable loads of under 8,000 lbs. They are typically less expensive than rotary arm models and have a smaller footprint - a definite asset when space is at a premium.

THE WULFTEC ADVANTAGE:

- > Allen Bradley PLC for more flexibility
- > AC variable frequency drives and motors
- > Heavy-duty steel construction
- > NO-THREAD® powered pre-stretch carriage
- > Superior warranties



- > LIFETIME warranty on pre-stretch rollers' blue compound
- > 10-year warranty on structural frame
- > 10-year warranty on ring gear
- > 3-year unlimited cycle warranty (4-year for the SMLPA-200**** & SMHPA-300)

WE'LL KEEP YOU RUNNING AT PEAK SPEED

NON-CONVEYORIZED TURNTABLE MODELS

SMLPA-200

AN AUTOMATED SYSTEM THAT'S EXTREMELY AFFORDABLE AND EASY TO USE



SMLPA-200

- 65" diameter table
- Pneumatically-activated Cut & Wipe Film Treatment System
- Air compressor included -- no external air source required
- 32 non-metallic lube-free turntable supports for superior performance
- 5,000 lbs. weight capacity
- Up to 50 loads per hour
- Ramp accessibility

SMHPA-300

THIS EXTRA HEAVY-DUTY MODEL OFFERS EXCEPTIONAL TOUGH AND ACCURATE WRAPPING



SMHPA-300

- Extra heavy-duty, portable ring-gear driven high-profile turntable
- Proven Cut & Wipe Film Treatment System
- 8,000 lbs. weight capacity
- Up to 55 loads per hour

ALL THE BENEFITS OF AUTOMATION AT AN AFFORDABLE PRICE

www.wulftec.com

CONVEYORIZED TURNTABLE MODELS

WCA-150

COMPETITIVELY-PRICED RING-GEAR DRIVEN TURNTABLE

- Proven Cut & Wipe Film Treatment System
- Standard low wrapping film clamp
- Touch screen operator interface
- Forward conveying system
- Up to 50 loads per hour



WCA-150

WCA-200

THIS EXTRA HEAVY-DUTY MODEL IS PERFECT FOR SPACE-RESTRICTED AREAS

- Extra heavy-duty turntable with ring-gear bearing drive
- Close pitch roller conveyors for higher capacity and smoother transition
- Proven Cut & Wipe Film Treatment System
- Standard low wrapping film clamp
- Forward/reverse conveying system
- Up to 60 loads per hour



WCA-200

HAVE A SPECIFIC PACKAGING NEED? WE CAN HELP! VISIT WWW.WULFTEC.COM OR CONTACT YOUR WULFTEC DISTRIBUTOR



Allen Bradley PLC with touch screen panel for a wide range of options and program changes



AC variable frequency drives and motors for safe, reliable performance and minimal maintenance



20" NO-THREAD® powered pre-stretch carriage for quick, easy and safe film loading -- 50% to 300% pre-stretch for optimal film use and reduced costs



Cut & Wipe film treatment system eliminates the need to attach and cut film, minimizing operator involvement and guaranteeing a tight wrap with no film tail for worry-free transport



Dual chain carriage lifts

Our automatic turntable stretch wrappers wrap 2" from conveyor or turntable - guaranteeing a secure load

Why Compromise? Customize!

Our most popular options:

- 30" NO-THREAD® powered pre-stretch carriage: Larger web means you'll wrap faster and use less film
- Pop-up device: Lifts the load so the film can go under the pallet, securing the load right to the pallet
- Wrap height extension: Wraps loads exceeding 80" in height
- Dark load photoeye: Wraps dark or shiny loads that reflect light
- Turntable speed: Increases speed so you'll wrap more in less time
- Top platen: Stabilizes light and unstable loads
- Top sheet dispensers: Applies a protective plastic sheet on top of the load
 - Incycle top sheet dispenser protects against water ingress
 - Inline top sheet dispenser protects against dust