

## MSL

### Manual Sidedrive Low Profile Carton Sealer

The BestPack™ MSL is an operator fed, adjustable carton sealer designed to effectively seal very low-profile boxes, in addition to the standard array of carton sizes. The MSL can seal cartons a mere 2.5" high and the upper mast allows for an extra 4" carton height extension on the upper assembly.

Our MSL line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



## Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



Top & Bottom Seal

## Features

- Side Belt Drive
- Width/Height Adjustment on Either Side of Carton Sealer
- Seals Cartons as Low as 2.5" in Height
- Upper Side Compression Unit
- Adjustable Bed Height from 20.5" - 30"
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Exclusive Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm
- 3" Model Capable of Interchanging 2" or 3" Tape Heads
- Tape Roll Lengths: 1,000 yd., 1,500 yd., and 2,000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts

- Electrical On/Off Box can be Mounted on Either Side of the Carton Sealer
- Tool Kit & Operation Manual

## Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Locking Heavy-Duty Casters
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- 3-Flap Folder
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

# Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor  
w/ L-Bracket Stabilizer



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft.)
- Short Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Food Grade 304 Stainless Steel
- Carton Sealing Tape

## Machine & Carton Specifications

**110 Volts 60 Hz**  
Power Requirements

**Up to 40 Cartons/min.**  
Speed

**None**  
Air Requirements

**400 lbs**  
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.**	Shipping Weight (lbs.)
MSL22-2 <b>2" Tape Head</b>	(56.8") x (33.5") x (71.3")	(6.0" - U) x (5.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30")	Up to 40	400
MSL22-3 <b>3" Tape Head</b>	(56.8") x (33.5") x (71.3")	(6.0" - U) x (6.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30")	Up to 40	400

All specifications capable of customization.  
Information subject to change without notice.

U - Unlimited  
\* Outside Dimensions Only  
\*\* Based on 12" Long Carton