

CLICK HERE TO CONTACT TOMAR INDUSTRIES ABOUT OUR FREE TAPE HEAD PROGRAM

SECURE SEALS EVERY TIME

-

The ShurSEAL[®] Solution combines Shurtape[®] HP Series packaging tape with a PrimeLoc[™] tape applicator for better carton seals and packaging line efficiency. This innovative packaging solution delivers consistent and secure seals, carton after carton.





HP 100[®]

132°

F

HP 200[®]

HP 232[®]

HP 235

HP 300®

HP 400[®]

PrimeLoc Tape Applicators

- Unmatched wipe-down force via multiple, flexible wipe-down points
- Full utilization of the tape's adhesive to form secure, tamper-evident seals
- Optional folded-edge technology for added strength and no-knife opening feature
- Easily retrofitted to most case sealing equipment

- HP Series Packaging Tape
 Forms an instant, permanent bond with cartons
 Offers the highest holding power to fiberboard in the industry
 Performs reliably to the core

HP SER

RIES	PACKAGING TAPE	Thickness	Adhesion to Stainless Steel	Tensile	Holding Power to Fiberboard	Service Temperature Range
	Automated or manual sealing of lightweight cartons Easy unwind Instant, permanent bond Application temperature range of 35 F to 110 F 	1.6 mils	43 oz/in width	21 lbs/in width	10,000 min	20 - 150 F
	Cold temperature sealing of lightweight cartons • High performance in cold-temperature environments • Instant, permanent bond in sub-freezing temperatures • Application temperature range of 20 F to 75 F	1.6 mils	30 oz/in width	21 lbs/in width	10,000 min	-20 - 100 F
<u>()</u>	Automated or manual sealing of medium-weight cartons Superior performance Instant, permanent bond Transparent colors for inventory identification Application temperature range of 35 F to 110 F 	1.9 mils	44 oz/in width	27 lbs/in width	15,000 min	20 - 150 F
	 Cold temperature sealing of light to medium-weight cartons High performance in cold-temperature environments Instant, permanent bond in sub-freezing temperatures Application temperature range of 20 F to 75 F 	1.9 mils	30 oz/in width	27 lbs/in width	10,000 min	-20 - 100 F
)	Automated or manual sealing of medium-weight cartons High holding power on highly recycled or 100% PCW/OCC cartons Tough, aggressive and consistent case sealing performance Adheres well to recycled corrugate, recycled paper and a variety of other substrates Application temperature range of 35 F to 110 F 	2 mils	50 oz/in width	27 lbs/in width	15,000 min	20 - 150 F
	Automated or manual sealing of medium-weight cartons Performance grade Instant, permanent bond Application temperature range of 35 F to 110 F 	2.2 mils	47 oz/in width	30 lbs/in width	20,000 min	20 - 150 F
	Automated or manual sealing of large, heavy-weight cartons High performance Instant, permanent bond Ideal for high-speed, critical-closure production lines Application temperature range of 35 F to 110 F 	2.5 mils	54 oz/in width	33 lbs/in width	25,000 min	20 - 150 F
	Automated or manual sealing of heavy-duty cartons Premium grade Instant, permanent bond Ideal for use on demanding packaging lines on cartons with high recycled content Application temperature range of 35 F to 110 F 	3 mils	58 oz/in width	42 lbs/in width	30,000 min	20 - 150 F







 \odot

Multiple patents pending by PrimeLoc, a trademark of PrimeLoc Packaging, Inc *Shurtape is an authorized distributor of PrimeLoc Packaging, Inc

ISO 9001 CERTIFIED QUALITY SYSTEM © 2014

THE SHURSEAL SOLUTION

Aggressive Adhesive For Highest Holding Power



FOR SECURE SEALS EVERY TIME

We are your case sealing partner – with a vested interest in your case sealing success.

This program is designed to address your issues with packaging line downtime and insecure seals -balancing your retrofit needs with your tape consumption.

Contact us to schedule an evaluation of your case sealing equipment - our team will identify potential issues and solutions, demonstrate how The ShurSEAL® Solution can deliver secure seals, as well as review potential cost savings that could be achieved by switching to The ShurSEAL[®] Solution.

CLICK HERE TO CONTACT TOMAR INDUSTRIES ABOUT OUR FREE TAPE HEAD PROGRAM

WHY USE THE Shurseal solution?

The ShurSEAL® Solution is a carton sealing system that combines Shurtape HP Series packaging tape with a PrimeLoc tape applicator to deliver consistent and secure seals, carton after carton.

Insecure seals can cause problems along the supply chain, resulting in production issues, downtime and higher costs due to reworks, in addition to increasing the risk of product damage, contamination and theft caused by cartons popping open. Even using a knife to open a carton can lead to product damage and injury due to knife cuts. The ShurSEAL® Solution is designed to deliver quality, secure seals, while also maximizing packaging line efficiencies to keep them running longer and faster.

And, while replacing packaging equipment can be costly and slow, The ShurSEAL[®] Solution is easily retrofit to a variety of automated machines, including most major brands of case sealers, to deliver secure seals without expensive capital expenditures and time-consuming changeovers.



Wipe-Down For Stronger Seals

Folded-Edge

For No-Knife Opening

IRCED STRENGTH. READY Folded-edge technology folds the edge of the tape along the length of the carton, reducing the possibility of nicks and tears along the tape seal, and allows the carton to be opened without the use of a knife.



ALERT SYSTEM

Operators have more control on the packaging line, with the ability to immediately address case sealing issues. Prime-Alert offers visual and audible alerts to signal five case sealing issues: low tape, no tape, broken tape, uncut tape and case jams.



CARTONS SEALS STAY INTACT

Delivers full utilization of the tape's adhesive via multiple, flexible wipe-down mechanisms, resulting in increased fiber tear for tamper evident security; even on under-filled cartons.



RETROFIT

The ShurSEAL Solution can be retrofitted into over 300 machines including most major brands of case sealers; revitalizing your older equipment with minimal capital expenditure to give you the best automated case seal in the industry.