

itape



Shown with optional infeed table

UA 262024-SB

UNIFORM AUTOMATIC CASE SEALER

Interpack's UA Series Case Sealers are adjustable, operator free machines that process same sized RSC style cases. These machines are required when production flow rates exceed manual processing or when automatic case packing is utilized. The UA 262024-SB offers upgraded side belt drive and processes the widest range of cases. Every Interpack™ Case Sealer comes with an ET 2Plus tape head with adaptive technology to provide optimal tape application and wipe down to each of the three taped panels of the case.

When you compare features, benefits and value, Interpack™ Case Sealers are the right choice for operators, plant engineers, maintenance and purchasing.



ET 2Plus tape head


MACHINE FEATURES & BENEFITS

- Compact 65" frame conserves floor space
- Full operating range versus competitive products
- Side belts capture the case between 2 moving belts to positively process the widest range of sizes
- Twin 1/3 HP drive motors for 24/7 operation
- Simple case size set up
 - Operator adjusts for case width & height
 - Machine self-adjusts to new case length
- Standard interlocking safety shields
- Standard indexing gate
- Slide & lock upper head simplifies case size set up
- Floating upper head processes compressible overfills
- Offset tape heads process cases as low as 3 1/2" tall
- Multi-wheel top squeezer standard

THESE MACHINES ARE ENGINEERED TO PROVIDE:

- World class performance features
- Heavy duty construction for 24/7 operation
- Ergonomic, user friendly operation and case size set up

Scan for more information on Interpack's UA Series, including CAD drawings, manuals and videos!



800-474-8273 | itape.com



PRODUCT ATTRIBUTES

CHARACTERISTICS	UA 262024-SB	UA 262024-SB/3
Min Case (L x W x H)	6" x 3.5" x 3.5"	6" x 4.5" x 3.5"
Max Case (L x W x H)	26" x 20" x 24"	26" x 20" x 24"
Case Weight	0 - 85 lbs	0 - 85 lbs
Belt Speed	82 ft/min	82 ft/min
Electric	110v., 1ph., 60hz., 6A., (2 x 1/3HP)	110v., 1ph., 60hz., 6A., (2 x 1/3HP)
Compressed Air Requirements	60 PSI	60 PSI
Tape Width	36 - 48 mm (1.5" - 2")	48 - 72 mm (2" - 3")
Conveyor Height	24" - 30"	24" - 30"
Machine Weight	905 lbs crated	905 lbs crated
Machine Dimensions	65.25" x 49.5" x 72.25"	65.25" x 49.5" x 72.25"



3-wheel top squeezer



Tip-up top tape head eases roll replacement



Offset tape heads process cases as low as 3.5"



Twin 1/3 HP gear motors to process up to 85 lb cases



No case length adjustment necessary



Single handle locks upper head to both columns



Optional swivel & locking casters



Standard interlocking safety shields (operator side)



Standard indexing gate



Infeed sensor



Self-tensioning & self-tracking drive belts simplify belt replacement



Side belt drive secures the case during processing

OPTIONS & ACCESSORIES

- Secondary E-stop
- 3-inch wide tape heads
- Heavy-duty casters
- ET Xtreme™ tape heads

DID YOU KNOW?

IPG® is the only North American manufacturer of all 3 types of pressure-sensitive adhesives. Combine Interpack™ machinery and IPG long roll pressure-sensitive tape for greater value. Contact your authorized IPG distributor for details.



Scan for more info or visit itape.com/machines

