i tape with (109)

Shown with optional in-feed table, exit table & casters.

USC 2020-SB Uniform Semi-Automatic Case Sealer

Interpack's USC grade of case sealers are part of the USA SERIES Uniform Semi-Automatic family. The USC 2020-SB is designed and constructed for low to medium volume applications. They are adjustable, operator fed machines that process same sized RSC style cases.

Every Interpack[™] Case Sealer comes with an HSD 2000-ET II tape head with adaptive technology to provide optimal tape application and wipe down to each of the 3 taped panels of the case.

When you compare features, benefits and value, Interpack[™] Case Sealers are the right choice for operators, plant engineers, maintenance and purchasing.

These machines are engineered to provide:

- Economical cost
- Compact footprint to conserve valuable floor space
- Ergonomic, user-friendly operation and case size
 set up

Scan for more information on Interpack's USA Series, including CAD drawings, manuals and videos!



FEATURES & BENEFITS

- Compact design conserves valuable floor space
- 3mm steel formed and welded construction
- 2" side belt drives with belt over roller technology
- 1/4 HP motors will process up to 65 lb cases
- · Dual column for maximum processing stability
- Threaded rod upper head adjustment
- Reversible controls for left or right handed operation
- Tilt up upper tape head for easy roll replacement





Available in food grade 302-304 stainless steel and NEMA 4 electrics, which is ideal for non-caustic washdown applications



TAPES & FILMSPACKAGING PRODUCTS & SYSTEMSBUILDING MATERIALSENGINEERED COATED PRODUCTS

USC 2020-SB

Model	Min Case (L × W × H)	Max Case (L × W × H)	Case Weight	Belt Speed	Electric	Tape Width	Conveyor Height	Machine Weight	Machine Dimensions (L × W × H)
USC 2020-SB	6" × 4" × 5"	Inf × 20" × 21.5"	0 – 65 lbs	75 ft/min	110v., 1ph., 60hz., 6A., (2 × ¼HP)	36 – 48 mm (1.5" – 2")	24" – 30"	445 lbs crated	36" × 38.5" × 67"
USC 2020-SB/3"	6" × 5" × 5"	Inf × 20" × 21.5"	0 – 65 lbs	75 ft/min	110v., 1ph., 60hz., 6A., (2 × ¼HP)	48 – 72 mm (2" – 3")	24" – 30"	445 lbs crated	36" × 38.5" × 67"

Top squeezers close to 6.5"

i tape with (ipc





MACHINERY: 800-972-4675

www.itape.com | info@itape.com