

ROTOTECH 708 CS SEMI-AUTOMATIC STRETCH WRAPPER

Perfect for heavy and unstable loads. Save time and increase productivity with the automatic cut, clamp and spreading system (CS) which keeps your operator on the fork truck.

- CUBE Technology will reduce your film usage by 30% to 55%, improve your load containment and reduce potential product damage.
- Our Heavy Duty Cut, Clamp and Spread System can save you an average of 30 seconds of labor per load. For the average customer, this translates to \$60,000 in labor savings!



*Shown with Top Platen option (non-standard)



Performance features:



AUTOMATIC FILM CUT, CLAMP AND SPREADING SYSTEM (CS)

The cut, clamp and spreading system ensures a perfect adherence of the final round of film on the wrapped product. The new aluminum clamp controlled by a pneumatic cylinder holds the film clearly and without slippage during cutting.

COLOR TOUCH SCREEN

The control panel has been newly designed, adopting it to a touch screen. Thanks to the large 7" color touch screen this new panel allows you to create programs simply and immediately. It is supplied with more memory to record up to 12 different programs (6+6 with Multilevel Control).



Rconnect Ready

Provides usage and performance data via the cloud, putting performance monitoring & optimization at your fingertips. Utilization drastically reduces downtime by giving you informational transparency, allowing you to connect with your machines remotely to investigate alarms, adjust



Horizontal Rotating Extendable Arm

First adjustable rotating arm machine. Adjust length of rotating arm to wrap products with maximum dimensions 55" x 55". Reduce by adjusting minimum length to wrap products only 16" x 16".



Rototech 708 CS Specifications

Performance Criteria

Production Speed:

Up to 35 LPH

Wrap Arm Speed:

12 RPM

Rotary Arm Drive:

1 HP VAC

Load Capacity

Maximum Load Dimensions:

55" W x 55" L x 80" H

Maximum Load Weight:

Unlimited

Film Delivery System

- Power Variable Stretch 150 – 400%
- Containment Force: Load Cell
- Film Carriage Motor: 1/3 HP VAC
- Height Sensing: Automatic photo eye
- Film threading: patented S-Pattern
- Corner Compensation: Load Cell
- Standard Film Width – 20" (30" option)

Operator Interface

- Touch screen HMI control panel
- 12 programmable wrapping menus

Safety Features

- Safety Bumper Warning Light
- Safety Alarm
- CE Compliant, UL, CUL

Utility Requirements

Voltage: 115V, 20 AMP, 60 Hz, 1 PH

Air: 90 PSI

Warranty: 1 Year