



eLUMINATE

Ultra Compatible Zinc Free Finish



Availability:

| Packaging | Item # |
|----------------|--------|
| 4-1 F Gal.: | 109147 |
| 2-2.5 Gal.: | 109162 |
| Pail/ 5 Gal.: | 109158 |
| Drum/ 55 Gal.: | 115567 |

Vinyl Tile
Azulejo del vinilo

Linoleum
Linóleo

Terrazzo
Terrazo

Concrete
hormigón

Slate
pizarra

DESCRIPTION


A new generation floor finish formulated with patented zinc free polymer technology that is designed to work with any type of maintenance program. This finish provides high initial gloss and unmatched gloss retention. New chemistry demonstrates exceptional soil resistance and color retention that far exceeds the leading commercial zinc containing finishes and allows the finish to form good film even in poor drying conditions. This environmentally preferable finish meets today's need for a product that contains no zinc or other heavy metals that can be harmful to wastewater treatment systems.



MISCO
1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568
www.miscoproducts.com



Ultra Compatible Zinc Free Finish



Scan for product's
Safety Data Sheet

FEATURES

- Cutting edge zinc free polymer
- Exceptional quat & soil resistance
- Low ammonia
- UL Environment Certified

BENEFITS

- Prolongs floor finish life cycle
- Long term film clarity
- No odor
- Dramatically improves recoatability
- Meets LEED certification and other green regulated mandates

AREAS OF USE:

- Supermarkets
- Retail stores
- Healthcare facilities
- Hallways
- Office buildings
- Vinyl tiles
- Linoleum
- Terrazzo
- Slate
- Concrete

DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely. If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four to five coats is ideal initially, depending on the condition of the floor and desired gloss.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly. This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and federal regulations

SPECIFICATIONS:

Color:
Milky White

Odor:
Fragrance Free

pH:
8.0 — 9.0

Non-Volatile Solids:
22%

Coverage:
1800 — 2200 ft² / gal.

Recommended Coats:
4 - 5

Dry/Recoat Time:
30 minutes min.

Maintenance Schedule:
Weekly burnish or spray buff

Slip Resistance:
0.5 min. by ASTM D2047

Storage/Stability:
1 year

Weight Per Gallon:
8.54 lbs./gal.

Freeze/Thaw Stability:
3 cycles

HAZARD STATEMENTS

May be mildly irritating to eyes and skin.

PRECAUTIONARY STATEMENTS

Do not get in eyes, on skin, or on clothing.

Keep out of reach of children.

Wash thoroughly after handling.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

STORAGE

Keep container closed to prevent drying out.

Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities.

Close container after use.

SPILL/LEAK

Avoid walking in product. Wipe up or otherwise flush to sanitary sewer.

DISPOSAL

Dispose of contents/container in accordance with local, state and federal regulations.

INGREDIENTS

Acrylate Copolymer - (N/A), Diethylene Glycol Ethyl Ether - (111-90-0), 2,5-furandione, polymer with propene - (25722-45-6), Tributoxethyl Phosphate - (78-51-3), 2,2,4-trimethyl-1,3-pentanediol diisobutyrate - (6846-50-0), Oxidized Polyethylene - (68441-17-8), Water - (7732-18-5)



1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568

www.miscoproducts.com